







Department of Transport

KITEBOARDING AND WINDSURFING SAFETY EQUIPMENT

		Protected Waters lakes, rivers & inlets	Unprotected Waters			
			0 - 400 Metres	400m - 2 Nautical Miles	2 - 5 Nautical Miles	Over 5 Nautical Miles
 Lifejacket A lifejacket bearing the label Level 50S (or higher) with the Australian Standard AS 1512, AS 4758, AS 1499, AS 2260, ISO 12402 as prescribed opposite.	<i>Recommended</i>	<i>Recommended</i>	✓	✓	✓	
			TO BE WORN			
 Red and Orange Flares (<i>in-date</i>) At least two hand held red flares and two hand held orange flares must be carried. Two parachute flares may be carried in lieu of the two hand held red flares and a smoke canister may be carried in lieu of the smoke flares.	—	—	✓	<i>Recommended</i>	✓	
			or		✓	✓
 Distress Beacon (<i>in-date</i>) A 406 MHz PLB or EPIRB registered with AMSA bearing the standard AS/NZS 4280.1 or 4280.2 must be carried if proceeding more than 2 nautical miles from the mainland shore or more than 400 metres from an island located more than 2 nautical miles from the mainland shore.	—	—	✓	✓	✓	
			—	—	—	—
 Parachute Flares (<i>in-date</i>) A minimum of two parachute flares must be carried if operating more than 5 nautical miles from the mainland shore or more than 1 nautical mile from an island located more than 5 nautical miles from the mainland shore.	—	—	—	—	✓	

✓ = Required

— = Not Required

Contact Number: _____

Alt. Contact Number: _____